

DECLARATION OF PERFORMANCE

NO:GRES 01

DRY- PRESSED CERAMIC TILE. WITH WATER ABSORPTION $E_b \leq 0,5 \%$ FOR
INTERNAL AND EXTERNAL WALLS AND FLOORINGS

NUOVA RIWAL CERAMICHE SRL, VIA GHIAROLA NUOVA 101
41042 FIORANO MODENESE (MO) ITALIA

SYSTEM 4

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 FL/A1	EN 14411:2012
Release of dangerous substance, for:		
_ Cadmium	NPD	
_ Lead	NPD	
Breaking Strenght	>1300 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	1N/mm ²	
Thermal Shock Resistance	PASS	
Durability for:		
_ Internal Use:	PASS	
_ Exetrnal Use: freeze-thaw resistance	PASS	

The performance of the product identified in point 1 is in conformity with the declared performaces in point 6. This declaration of performance is issued under the sole responsibility of the manufacture identified in point 3.

Signed for and on behalf of the manufacturer by :

ALBERTO ALBONETTI
(Technical Director)



Fiorano Modenese 01/09/2015